



TECHNICAL SPECIFICATIONS

J-50 B2

Cordless finishing nailer

Cordless finishing nailer, ideal for carpentry, fixing panelling, skirting boards, frames, mouldings, etc.



L 269
h 89
L 287



2,10 kg



2,5 Ah Li-ion
18 V



110



15 - 55 mm



1,20 mm

J-50 B2 | TECHNICAL SPECIFICATIONS

Cordless finishing nailer

Code **12B1250B2**

Description


Cordless finish nailer, ideal for carpentry, fixing panelling, skirting boards, frames, mouldings, etc.

| | |
|--------------------------|---------------------------------|
| Dimensions (L/l/H) (mm) | 269 / 89 / 187 mm |
| Weight (kg) | 2,10 kg |
| Firing | Coup par coup / Rafale |
| Magazine capacity | 110 nails |
| Projectile type | Nail J |
| Projectile length (mm) | 15 - 55 mm |
| Projectile diameter | 1,20 mm |
| Firing rate | up to 3 to 4 shots/second |
| Maximum shots per charge | 1 200 shots/charge |
| Battery type | Li-ion 18 V - 2.5 Ah |
| EAN code | 3660601092452 |
| Supplied with | Case, 2 batteries and 1 charger |

Projectiles

Nail J

15 - 50 mm
ø 1.20



Other version available

> code : **12B1250X** - Supplied without case, battery or charger



Advantages

- > Supplied in a case with 2 batteries and 1 charger
- > Powerful brushless motor, 20 J
- > Quick release nose, no tools required
- > 6 levels of electronic depth adjustment
- > 1,200 shots per battery charge
- > Compact design and perfect balance
- > Non-slip handle
- > Compatible with 2.5 and 5 Ah batteries in the range

Noise level and vibrations

| | |
|---|--------------------|
| Noise characteristics in accordance with standard | EN 12549+A1 |
| A-weighted sound pressure level at the workstation | 76 dB |
| A-weighted sound power level | 87 dB |
| C-weighted instantaneous peak sound pressure level at the workstation | 79 dB |
| Vibration value according to EN ISO 28927-13 | 2,31 m/s² |

Related products

| Battery | Battery | Charger |
|------------------|------------------|-----------------|
| 18 V - 2.5 Ah | 18 V - 5.0 Ah | 18 V |
| code : 12BAT1825 | code : 12BAT1850 | code : 12CHRG18 |

